

Protectli Firewall Appliances

Protectli 5G Modem (external) - IDG450



Protectli is the premier manufacturer of firewalls in the United States, distributing worldwide. It uniquely provides a trusted hardware platform with advanced firmware protection.

Trusted Hardware Small and compact form factor, built fanless. Antennas, MicroUSB cable (power only), and RJ45 cable are included. Plugs directly into the Vault. Excellent for internet failover: Never lose network connectivity again. Perfect as primary backup and WAN backup.

Supported 5G Bands

Country	Mobile Operator	5G Bands	LTE	GSM Band
Europe	Various	B1/B2/B3/B4/B5/B7/B8/B12/B 13/B14/B17/B18/B19/B20/B2 5/B26/ B28/B29/B30/B32/B66/B71 TDD-LTE Bands: B34/B38/B39/B40/B41/B42/B 43/B48	B1/B2/B3/B4/B5/ B7/B8/B12/B13/ B14/B17/B18/B1 9/B20/B25/B26/ B28/B29/B30/B3 2/B66/B71	-

IDG450 Series Data Sheet

Model	IDG450
Description	Protectli 5G Modem (external)
Device Interface	 5G Module: 1*5G/LTE, 3GPP Release 16, 1*micro SIM slot Ethernet: 1*RJ45 2.5 Gigabit Ethernet Power Input: DC 5V (USB Type C) Antenna Connectivity: 4*SMA (F)-5G /LTE
WAN & Uplink	 WAN: Cellular, NAT or Bridge mode Cellular: 5G/LTE, IPv4/6 Network Monitor: ICMP
Protocol	 LAN & VLAN: DHCP Server IPv6: Cellular IPv6

Security	Firewall: NAT SPI Firewall with Stealth Mode
Administration	Web UI
Environment	 Operation Temperature: -30°C-145°C (-30°C-60°C) Storage Temperature: -40°F-185°F (-40°C-85°C) Humidity: 10%~95% (non-condensing)
Certification & Carrier Approval	• CE • PTCRB
Chassis	Fanless, Aluminum, Black
Chassis Dimensions	3 x 3 x 1 in, 7.4 x 68.6 x 2.6 cm
Weight	0.3 lbs, 0.17 Kg

Front View








Top View



Wall Mount Brackets (optional)



DIN Rail Kit (optional)

